

Current status of dark matter searches at the Boulby facility

Boulby Programme
Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future

*N.J.T.Smith
CCLRC Rutherford Appleton Laboratory
On behalf of Boulby DM Collaboration*

Boulby Programme


Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future

Boulby DM Programme

Collaboration

University of Edinburgh
Imperial College, London
CCLRC Rutherford Appleton Lab.
University of Sheffield

Coimbra University
ITEP
LLNL
Occidental College
Temple University
Texas A&M
UCLA



Boulby Programme
Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future


A place to find WIMPs

- Surface facilities
 - **Workshop, offices, etc.**
- Underground facilities
 - **New clean area, upgrade existing**
- Opened April '03 by Lord Sainsbury
 - **With a place in the Sun**



Boulby Programme
Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future

NaIAD Array



- NaIAD: 8 NaI(Tl) crystals totalling 65kg
 - **6 unencapsulated, 2 encapsulated**
 - **Light yield 5 - 9 p.e./keV**
 - **Temperature stabilised to 0.1°C**
 - **Threshold 1-1.5 keV**
 - **DAQ based on Acquiris C-PCI 100MHz digitisation (replaced Lecroy DSO)**
- Unencapsulated crystals
 - **Removal of fast anomalous events (radon induced low energy alphas)**
 - **Operated in dry nitrogen, 1cm PTFE cage, quartz light guides**

Boulby Programme
 Boulby Facility
 NaIAD Status
 ZEPLIN I Status
 ZEPLIN III Status
 ZEPLIN MAX Future


NaIAD: full noise suppression

- Asymmetry cuts in PMT amplitude and Δ (2 PMT systems)
- Use of 'DAMA' type cuts on pulse shape
- Surface plot of events (all energies) in DM74 data run. Parameters P1 and P2 are as follows:


$$P1 = (PE_{600} - PE_{100}) / PE_{600}$$

$$P2 = PE_{50} / PE_{100}$$

Np.e. in 600ns




DM74 Time Constant Distribution 4-6 keV





Time constant distribution after noise rejection

Boulby Programme
 Boulby Facility
 NaIAD Status
 ZEPLIN I Status
 ZEPLIN III Status
 ZEPLIN MAX Future

NaIAD: Limits






Scalar cross section



2000/01 Spin dependent cross section

Boulby Programme
 Boulby Facility
 NaIAD Status
 ZEPLIN I Status
 ZEPLIN III Status
 ZEPLIN MAX Future

ZEPLIN I



5kg LXe target (3.1kg fid)
 3 PMTs
 Cu construction
 Polycold cryogen cooling


1 tonne Compton veto
 PMT background tag
 Gamma calibration
 Neutron monitor

Boulby Programme
Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future


S3 Fiducial volume cut

Reduce the background

Project normalised amplitudes PMT1,2,3 onto plane - S3




Trigger condition is set to 'free-run'



Boulby Programme
Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future

Uniformity, light collection


- Part of detector response matrix
 - **17% best, 14% bulk**
 - **Falls to 4% below Xe delivery pipe**
- Light collection simulations allow S3 calculations
- S3 cut < 0.408
 - **(66% on 1: $0.5 + 0.5/3$)**
- Fiducial volume 3.1kg
 - **(excluding turrets + ~1cm below)**



Boulby Programme
Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future

ZEPLIN I Energy Resolution

57 Co Calibration





Boulby Programme
 Boulby Facility
 NaIAD Status
 ZEPLIN I Status
 ZEPLIN III Status
 ZEPLIN MAX Future

Z1 Energy Calibration

Multi-source calibration
 Variation in yield commensurate with
 volume response matrix

Geant4 Simulation of ^{57}Co calibration
 With/without energy resolution







Boulby Programme
 Boulby Facility
 NaIAD Status
 ZEPLIN I Status
 ZEPLIN III Status
 ZEPLIN MAX Future

ZEPLIN I Discrimination

Remove the background

- Surface neutron calibrations to 3keV_{ee}
- Surface ambient neutrons below 10keV_{ee}
- Ratio held at $0.5 < 7\text{keV}_{ee}$ (conservative)
- Fitted \square density function in $1/\square$
- Underground gamma calibration to 2keV
- Consistent with beam tests ($0.6@15\text{keV}_{ee}$)
- Check on efficiency of PMT noise cuts




constant ns

Boulby Programme
Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future

ZEPLIN I low Kr level

- Background with standard Xe:
estimated $^{85}\text{Kr} < 10^{-17}$
atoms/atom, spec: 5ppm
- Now using Xe with 40ppb Kr
impurities (specification).
- 16 d of high light yield data
2.5 pe/keV (vs 1.4-1.8 before)

- Background reduction
- Source of remaining?





No Cuts

Boulby Programme
Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future

ZEPLIN I Data Runs

- 3 data sets, 91 day livetime, 290kg.days
 - Light yield >1.5 p.e./keV (2.5 p.e./keV best)
 - Gamma calibration data from contemporaneous veto events and extended source calibration
 - Neutron calibration from surface data
- Analysis: look for deviation at end of tail




Boulby Programme
Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future

ZEPLIN I SI limit

Preliminary. Paper in preparation


- Based on lab neutron discrimination
 - **To be re-done underground**
- Nuclear physics
 - **Quenching (0.2@8keV_{ee})**
 - **Form factor**
- Efficiencies incorporated
 - **Poisson trigger**
 - **Light collection response**
 - **Energy resolution**
 - **PMT noise cuts**
 - **Fiducial volume (S3)**
 - **Dead-time**
- ‘Standard’ DM model



Boulby Programme
 Boulby Facility
 NaIAD Status
 ZEPLIN I Status
 ZEPLIN III Status
 ZEPLIN MAX Future

Two phase discrimination

'Low' drift field in liquid bulk - recombination occurs for nuclear recoils




Boulby Programme
Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future


Two phase discrimination

'High' drift field in liquid bulk - charge separation occurs for nuclear recoils

- 1kg Prototype
- Alpha calibration



Depth Information
For given drift fields




Relative size gives discrimination

Boulby Programme
Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future




ZEPLIN III

- 2 phase detector, 31x 2" PMT
 - Reverse field for PMT Xrays
 - Position sensitivity
 - PMTs in liquid
- High E-field to extract ionisation from nuclear recoils
 - Nuclear recoil S1 and S2
- 7kg target under construction
- Deployment 2004
- Study for 1 tonne
 - Low threshold (S2 trigger)
 - High light yield
 - Fiducialisation, imaging



Boulby Programme
Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future

Zeplin III Status



Boulby Programme
Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future

ZEPLIN MAX and Future

- ZEPLIN MAX detector
 - 1 tonne active volume, target sensitivity 10^{-10} pb
 - Input from ZEPLIN I operational experience
 - ZEPLIN II/III progenitors for design info
- Issues
 - Operational mode
 - Readout technology (U/Th background)
 - Background suppression
 - active muon/neutron veto
 - passive shielding
 - detector design
 - purity requirement




Boulby Programme

Boulby Facility
NaIAD Status
ZEPLIN I Status
ZEPLIN III Status
ZEPLIN MAX Future

Summary and Future

- Facility construction completed
 - **Neutron measurements underway**
- NaIAD array fixed operation
- ZEPLIN I
 - **Extended underground Compton calibration**
 - **Surface neutron calibration reanalysis**
 - **Additional 50kg.days from IDM02 data**
 - **Higher light yield**
 - **Efficiency calculation and simulations**
- Future ZEPLIN I Programme
 - **Underground n calibration**
 - **Full MC cross check of efficiencies**
 - **Low energy xenon quenching measurement**
- ZEPLIN II/III/MAX
 - **Commissioning/operation of progenitors**
 - **R&D+Design for tonne scale detector**



Preliminary